

山特维克圆锥破碎机参数



Model	Former name	Capacity t/h	Max feed size mm (inch>	CSS rangemm (inch>	Max permitted power kW (hp>	Total weight kg (lbs>
CH420	H2800	25-130	29-135 (1 1/8-5 1/4>	4-35 (5/35-1 1/4>	90 (120>	5300 (11700>
CH430	H3800	35-220	35-185 (1 1/2- 7 1/2>	5-41 (5/16-1 1/2>	132 (177>	9200 (20300>
CH440	H4800	65-415	38-215 (1 3/8-8 1/2>	8-44 (1-1 3/4>	220 (295>	14300 (31500>
CH660	H6800	145-660	50-275 (2 1/2- 10 3/4>	13-51 (1/2 - 2>	315 (422>	24200 (53352>
CH870	H7800	280-1510	80-300 (3.2- 11.8>	10-70 (0.4- 2.8>	520 (697>	50000 (110200>
CH890		268-2595	370 (14.6>	16-70 (0.6- 2.8>	750 (1000>	77000 (169800>
CH895		178-1170	120	10-51	750	81000

			(4.7>	(0.4-2>	(1000>	(178600>
CS420 S2800		70-170	200-240 (8-9 1/2>	19-38 (3/4-1 1/2>	90 (120>	6800 (15000>
CS430 S3800		90-345	235-360 (10-14>	19-51 (3/4-2 1/8>	132 (177>	12000 (26400>
CS440 S4800		195-600	300-450 (12-18>	25-54 (1-2 1/8>	220 (295>	19300 (42500>
CS660 S6800		320-1050	500-560 (20-22>	38-83 (1 1/2- 3 1/4>	315 (422>	35700 (78705>
Discontinued model						
CH880	H8800	310- 2130	75-370 (2.9- 14.6>	8-70 (0.3- 2.8>	600 (804>	70000 (154300>

山特维克圆锥破碎机型号参数:

	最大装机功率	最大给料粒度	总重量	紧边排矿口	处理能力
	kw(hp)	mm(inch)	kg(lb)	mm(inch)	mtph(stph)
CH420	90	135	5 300	4-32	27-128
	(121)	(5.3)	(11 700)	(0.1-1.3)	(29.8-141.1)
CH430	132	185	9 200	6-38	48-208
	(177)	(7.3)	(20 300)	(0.2-1.5)	(52.9-229.3)
CH440	220	215	14 300	8-44	90-395
	(299)	(8.5)	(31 500)	(0.3-1.7)	(99.2-435.4)
CH660	325	275	24 200	13-51	211-662
	(422)	(10.8)	(53 352)	(0.5-2.0)	(233-730)
CH870	520	300	50 000	10-70	230-1512
	(697)	(11.8)	(110 200)	(0.4-2.8)	(309-1887)
CH880	600	370	70 000	8-70	300-2128
	(804)	(14.5)	(154 300)	(0.3-2.8)	(341-2346)



申明：

所有资料为本人收集整理，仅限个人学习使用，勿做商业用途。